

Overview

The **DT3600-150** Dual Vision Day/Night Surveillance Camera is the ultimate security product designed for long range surveillance in total darkness and extreme conditions. It is powerful system with a thermal and a night CCTV cameras, and controlled and view image through network.

With the state of art passive infrared thermal seeking technology and a 640x480 uncooled FPA detector, and a 2M pixels high resolution visual CCD, the DT3600-150 camera is equipped with heavy duty pan/tilt driver, long range laser illuminator and integrated thermostat controlled heater for adverse environment conditions.

Key Features

- Dual Vision, Thermal and Visual
- 640x480 high resolution FPA
- IP network control and image view
- 1000mm visual zoom lens
- Thermal continuous 150mm zoom lens
- 2MP resolution, day/Night CCD with laser illumination

Performance Optional & Accessories

- Thermostat controlled heater
- Pan and tilt drive
- Laser illuminator
- 500mm visual zoom lens (optional)
- 100/200mm thermal zoom lens (optional)
- Onvif compliant
- Milestone* compatibility fully tested and Verified

Product Image



Picture shown camera with pan/tilt and laser illuminator

Application

- Bridges ; Airports; Seaports; Subways
- Border & Perimeter security
- Surveillance applications
- Government facilities



Specifications

Distance	Visual camera	Day vision 5.5km, night vision up to 2.5km (Object: human)		
	Thermal camera	Object	Human (1.8m×0.5m)	Vehicle (2.3m×2.3m)
		Detection distance	6.3km	14km
		Recognition distance	1.6km	3.5km
Visual camera	Focal length	31.2~1000mm (15.6~500mm lens with 2X extender)		
	FOV	0.45°~13.75°		
	Sensor	1/1.8"Progressive Scan CMOS		
	Color mode	ICR double filter, day & night switch		
	Camera control	Auto gain control, auto white balance, supporting manual and auto day & night mode switch		
	Noise reduction	3D digital noise reduction		
	Code format	H.264/MJPEG/MPEG4		
	Video frame rate	50Hz:25fps(1920×1080),25fps (1280×720) 60Hz:30fps(1920×1080),30fps (1280×720)		
Thermal camera	Focal length	30-150mm, continuous zoom		
	Detector	640 x 480 uncooled microbolometer		
	Wave length	7.5-14um		
Laser illuminator	Beam	0.5°~27° continuous change		
	Source	Class 3B 15W laser 810nm		
	On/off switch	Auto/Manual control		
Pan/Tilt	Pan angle	360°, continuous rotation		
	Tilt angle	-45°~+45°		
	Pan speed	0.01°~ 12°/s		
	Tilt speed	0.01°~8°/s		
	Preset precision	±0.1°		
Environment	Operating	-40°C~+55°C		
	Storage	-50°C~+65°C		
	Encapsulation	IP66		
Network	Protocols	Onvif Conformant (V2.0/Profile S) TCP/IP/RTP/RTSP/HTTP/DNS/DDNS/DHCP/FTP/NTP		

* Milestone is a trade mark of Milestone Systems

Cantronic Systems (Canada) Inc.

Unit 8, 62 Fawcett Road

Coquitlam, BC V3K 6V5, Canada

Tel: 1.604.516.6667 /Tell Free: 1.866.391.6970 /Fax: 1.604.516.6618

Email: sales@cantronics.com Website: www.cantronics.com

Specifications are subject to change without prior notice.

Cantronic Systems (Canada) Inc. DS-TR-3600- Draft-1711A